

Technical Data Sheet



Guaranteed Values

Food service board (FSB)

Brand:

KomiBase Lux

Uncoated, bleached virgin-fibre board with a double layer fibre construction

Parameters	Unit of measure	Test method	Substance (g/m ²)					
			180	200	220	240	260	280
Substance tolerance	g/m ²	ISO 536	180±10	200±10	220±10	240±10	260±10	280±10
Caliper	µm	ISO 534	245±15	270±15	295±15	320±15	345±15	370±15
Moisture tolerance, min/max	%	ISO 287	6.0-8.0					
Scott plybond, min	J/m ²	TAPPI 569	230	200				
Bendtsen roughness (top side), max	ml/min	ISO 8791-2	600		1000		1400	
Brightness (top side), min	%	ISO 2470	80					
Brightness (bottom side), min	%	ISO 2470	70					
Cobb180 (top side), max	g/m ²	ISO 535	50					
Cobb180 (bottom side), min/max	g/m ²	ISO 535	50					

Information:

Mill's certificates

- ISO 9001
- ISO 14001
- ISO 45001

Test conditions: Guaranteed values after conditioning, measured at 50 ± 2% RH and 23 ± 1°C (ISO 187:1990)

System for verifying legal origin of the wood for this product complies with international standard **ISO 38200:2018** Chain of custody of wood and wood based products and Forest Certification Legal Origin standard

Product description:

Hot and cold drink cups. Packaging for food products. Disposable tableware for fast food, boxes, trays, plates, various containers and many others. Carton board without any polymer coating is used in "double wall cups"

Valid until: 31.12.2024 or until further notice